

HEALTH HAZARD INFORMATION

HEALTH EFFECTS

ACUTE:

- Swallowed: May cause irritation to mouth, throat and digestive tract. May cause nausea, vomiting and drowsiness. Large amounts may cause unconsciousness.
- Eyes: Irritant.
- Skin: Irritant. Avoid prolonged or repeated contact as this may cause dermatitis.
- Inhaled: Vapour is irritant to mucous membranes and respiratory tract. Vapour can affect the central nervous system and result in headaches and dizziness. High concentrations of vapour, if exposure is prolonged, may cause unconsciousness. Aspiration of liquid into the lungs can cause serious (even fatal) pneumonitis.

FIRST AID

- Swallowed: If swallowed contact a Doctor or Poisons Information Centre. Do not induce vomiting due to risk of aspiration. Give a glass of water and seek medical attention. If any suspicion of aspiration into the lungs (e.g. during vomiting) obtain medical advice immediately.
- Eyes: Wash thoroughly with water for at least 15 minutes and seek medical attention.
- Skin: Wash off with soap and water. Remove contaminated clothing and launder before re-use.
- Inhalation: Move to fresh air. Keep warm and at rest. Seek medical attention, if any suspicion of aspiration into the lungs.
- Advice to Doctor: Because of risk of aspiration, gastric lavage should only be undertaken after endotracheal intubation.

PRECAUTIONS FOR USE

- EXPOSURE LIMITS: Not established for product. Constituents TWA 8 hour, five-day week:
Xylene: 350mg/m³, 80ppm/ Toluene: 377 mg/m³, 100ppm
Methyl Ethyl Ketone: 445 mg/m³, 155 ppm.
- ENGINEERING CONTROLS: Avoid breathing vapour. Use in a well ventilated area. Local exhaust ventilation required. Spray apply in a spray booth fitted with an effective filtered exhaust system complying with local regulations.
- PERSONAL PROTECTION: Avoid skin and eye contact. Wear chemical resistant gloves, and goggles. Wear supplied breathing apparatus when spraying in confined areas or poorly ventilated areas.
- FLAMMABILITY: This material contains volatile and highly flammable solvents and must be kept away from all sources of ignition (open flames, sparks, pilot lights, furnaces, spark producing switches, etc). Use only in well ventilated areas and do not smoke. Keep containers firmly closed when not in use.

SAFE HANDLING INFORMATION

- STORAGE & TRANSPORT:** Store in a cool and well ventilated area away from heat and all sources of ignition. Store only in original or approved containers. Containers should always be kept closed in storage and properly labelled. This material is classified as Dangerous Goods Class 3 – must be stored and transported in accordance with State and Territory Dangerous Goods Regulations. SHIPPING NAME – UN 1263 PAINT GP II
- SPILLS & DISPOSAL:** Extinguish all ignition sources and ventilate area. Collect with absorbent material such as sand, earth or sawdust and place in closed containers. Ensure waste disposal conforms with local waste disposal regulations. After recovery and evaporation remaining soil may be disposed of to approved landfill or allowed to degrade insitu.
- FIRE/EXPLOSION HAZARD:** Highly flammable liquid. Combustion products include oxides of carbon, nitrogen and possibly toxic fumes. Vapour/air mixtures may ignite explosively. Use foam, CO₂, powder or BCF fire extinguishers. Hazchem code 3(Y)E.

OTHER INFORMATION

- TOXICOLOGY:** Not established for mixture. Hazardous ingredients:
Xylene Oral LD50 (rat): 4300 mg/kg,
Methyl Ethyl Ketone LD50 (rat): 2737mg/kg,
Toluol Oral LD50 (rat): 636 mg/kg.
Nitrocellulose Oral LD50 (rat): > 5000 mg/kg.
- CONTACT POINT:** KINGSTON PAINTS PTY LTD
33 – 35 ADRIAN ROAD
CAMPBELLFIELD VIC 3061
PH: (03) 9357 9396
EMERGENCY TELEPHONE NUMBER NOT AVAILABLE

This information is furnished without warranty, representation, inducement or licence of any kind except that it is accurate to the best of Kingston Paints Pty Ltd's knowledge or obtained by Kingston Paints Pty Ltd from sources believed by it to be accurate and Kingston Paints Pty Ltd does not assume any legal responsibility for use or reliance upon the same. Customers are encouraged to conduct their own tests. This information is non-controlled. It is the responsibility of the user to ensure that the issue is current.