



Kingston Paints Pty Ltd  
ACN 067 493 065 ABN 94 067 493 065  
(PO Box 327, Somerton, Vic., 3062)  
33-35 Adrian Road  
CAMPBELLFIELD, VIC., 3061  
Ph: (03) 9357 9396  
Fax: (03) 9357 9398

MATERIAL SAFETY DATA SHEET  
Health, Safety & Environment Data

DATE OF ISSUE: May 2010  
Page 1 of 3

### IDENTIFICATION

Hazardous according to criteria of Worksafe Australia

PRODUCT NAME:	FAST DRY GLOSS ENAMEL	UN Number:	1263
		Hazchem Code:	2 (Y) E
		Dangerous Goods Class:	3
		Subsidiary Risk Class:	N/A
		Poisons Schedule:	N/A
OTHER NAMES:	Aero Pack Spray Paint	Packaging Group:	II
PRODUCT CODE:	250- / 630- / 634- / 650- 4 Digit Suffix (denotes colour)		
USE:	A high gloss finish for drums and primed flat plate.		

### PHYSICAL DESCRIPTION/PROPERTIES

Appearance:	Coloured pigmented fast air drying enamels in organic solvent.
Boiling Point/Range (oC):	Unknown
Vapour Pressure:	Unknown
Weight Solids:	44 – 47%
Density:	1.13 – 1.15 kg/l

<u>HAZARDOUS INGREDIENTS:</u> <u>CHEMICAL ENTITY</u>	<u>CAS NO:</u>	<u>PROPORTION</u>	<u>TLV (units)</u>
Short Oil Alkyd Resin		10-60%	Unknown
Med Oil Alkyd Resin		<10%	Unknown
Aliphatic Hydrocarbons		10-20%	100ppm
Aromatic Hydrocarbons		<10%	100ppm
Inert Pigments		10-60%	n/a
Methyl Ethyl Ketoxime	96-29-7	<1%	Unknown

## HEALTH HAZARD INFORMATION

### HEALTH EFFECTS:

#### ACUTE

Swallowed:	Toxic if swallowed.
Eye:	Avoid splashes to the eye.
Skin:	Avoid contact with the skin. Prolonged contact may lead to dermatitis.
Inhaled:	Use with good ventilation and avoid inhalation of spray mist and fumes. Aspiration into the lungs can cause fatal pneumonitis.

#### FIRST AID:

Swallowed:	In the case of accidental ingestion, seek medical advice immediately. Do not induce vomiting.
Eye:	Irrigate with water for at least 10 minutes. Do not use thinners or solvents.
Skin:	Remove affected clothing. Wash skin thoroughly with soap and water. Do not use thinners or solvents.
Inhalation:	Remove to fresh air. Use artificial respiration if breathing stops.
Advice to Doctor:	Because of risk of aspiration, gastric lavage should only be undertaken after endotracheal intubation. For further information contact the poisons information centre.

## PRECAUTIONS FOR USE

VENTILATION:	Provide adequate ventilation during use.
PERSONAL PROTECTION:	Eye protectors (approved AS1337) should be used if there is a risk of splashes entering the eyes. Use chemically resistant gloves if needed to prevent repeated or prolonged skin contact.
FLAMMABILITY:	Flash Point <32°C. Keep away from sparks and naked flames.

### SAFE HANDLING INFORMATION

- STORAGE & TRANSPORT:** Store in banded area away from naked flames, as required for Flammable Liquid Class 3.2.
- SPILLS & DISPOSAL:** Spills may be absorbed in sand or inert materials. Consult the relevant local authority on waste disposal. Do not allow material to enter drains or waterways.
- FIRE/EXPLOSION HAZARD:** Fight fires with Carbon Dioxide foam or dry chemical extinguishers. Carbon monoxide may be evolved from incomplete combustion.

### OTHER INFORMATION

- \*\* IMPORTANT \*\*** Some colours contain lead and present a danger to young children from eating the dried paint, and should not be used on parts of buildings easily accessible to young children or on toys, furniture or any other articles likely to come within the reach of young children.
- CONTACT POINT:** KINGSTON PAINTS PTY LTD  
33 -35 ADRIAN ROAD  
CAMPBELLFIELD VIC 3061
- (03) 9357 9396  
Emergency Telephone Number Not Available

This information is furnished without warranty, representation, inducement or licence of any kind except that it is accurate to the best of Kingston Paints Pty Ltd's knowledge or obtained by Kingston Paints Pty Ltd from sources believed by it to be accurate and Kingston Paints Pty Ltd does not assume any legal responsibility for use or reliance upon the same. Customers are encouraged to conduct their own tests. This information is Non-controlled. It is the responsibility of the user to ensure that the issue is current.